


WOYE-L

4W-10W IP66



- Die-cast aluminum Housing with Clear Polycarbonate Diffuser.
- Corrosion resistance powder coated.
- Round, Square & Rectangle are available.
- Ingress Protection: IP66.
- Ultra-thin style.
- Asymmetric beam.

Technical Data

Installation method / 安裝方式 / Método de instalación	Surface Mounted / 明裝 / Montaje en superficie
Dimension / 尺寸 / Dimensión	Round: Dia 150 x 35mm Round: Dia 220 x 37mm Square: 150 x 150 x 35mm Square: 220 x 220 x 37mm Rectangle: 200 x 90 x 36mm
Input Voltage / 輸入電壓 / Voltaje de entrada	AC220-240V 50/60HZ
Power Consumption / 燈具功率 Consumo de energía	4W 6W 8W 10W
LED Driver Type / LED驅動款式 Tipo de controlador LED	Integrated / Remoted Type LED Driver-Refer to LED driver specification 參閱LED 驅動器規格 Consulte la especificación de controlador de LED 1. On/Off Switch AC220-240V 50/60HZ (Integrated Driver) 2. 0/1 -10V Dimming Driver AC220-240V 50/60HZ (Remoted Driver) 3. DALI Dimming Driver AC220-240V 50/60HZ (Remoted Driver)
Control Protocol / 控制協議 Protocolo de Control	0/1-10V / DALI
Beam Angle / 光束角 / ángulo de haz	Asymmetrical
Light Source Brand / 光源品牌 / Fuente de luz de marca	Lumileds / CREE / Osram
Lumen Maintenance LM-80 Reported by TM-21	L70> 54,000 Hours
LED Life / LED壽命 / La vida del LED	>100,000 Hours
Color Temperature / 色溫 Temperatura del color	2700K / 3000K / 4000K / 5000K / 6500K
Color Rendering Index / 顯色指數 Índice de reproducción cromática	> 80 > 90
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning elipse	Standard Deviation Colour Matching < 3 SDCM標準偏差配色< 3 SDCM Coincidencia de color estándar Desviación < 3 SDCM
Luminaire Efficacy / 燈具效率 La eficacia de la luminaria	25 LM/W (2700K) 30 LM/W (3000K) 35 LM/W (4000K) 35 LM/W (5000K) 35 LM/W (6500K)
LED Source Luminous Efficacy / LED光源光效 Fuente luminosa LED Eficacia	130 LM/W (2700K) 135 LM/W (3000K) 135 LM/W (4000K) 140 LM/W (5000K) 140 LM/W (6500K)
Housing materials / 外殼材料 Materiales de la carcasa	Die-cast aluminium housing with polycarbonate diffuser 壓鑄鋁外殼, 附聚碳酸酯擴散器 Carcasa de aluminio fundido a presión con difusor de policarbonato
Housing Color / 外殼顏色 / color de la carcasa	Black / 黑色 / Negro
Ingress Protection / 防護等級 Protección de ingreso	IP66
Impact protection / 衝擊保護 Protección contra impactos	IK10
Operating Humidity / 工作濕度 Humedad de funcionamiento	0~100%, non-condensing / 不結霜 sin condensación
Operating Temperature / 工作溫度 Temperatura de funcionamiento	-20 °C / +45 °C
Comply Testing Standard 符合測試標準 Cumplir el estándar de prueba	LED Luminaries: LVD: IEC/EN 60598-1;EN / IEC/EN 60598-2-2;IEC62471;IEC/EN 62031; IEC/EN 62493 ; IEC/EN 62471 (Risk Group 1) • LED Driver: IEC/EN 61347-1; IEC/EN 61347-2-13; IEC/EN 62384; IEC/EN 61000-3-2; • IEC/EN 61000-3-3;IEC/EN61574;EN 55015 ; IEC /EN 62384
Certification / 認證 / Certificación	    

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.

Example product code: [WOYE-L-6W](#)

WOYE-L - -
[Power Consumption](#)

Power Consumption	
Code	Description
4W	4W @ Round or Square or Rectangle
6W	6W @ Round or Square or Rectangle
8W	8W @ Round or Square
10W	10W @ Round or Square



