


AUDORA

9W Max



Housing: die-cast aluminium, powder-coated, designed as heat sink. Anti-glare reflector and diffusor system made of PC. LED module: high-power CREE LEDs Array, CRI>90, LM-80 performance approval >50,000 hours. Deep recessed design achieves super eye comfort.

Technical Data

Luminaire Type-安裝方式Tipo de luminaria

Pendant Mounted Type-懸垂式-Montado en colgante

Dimension-尺寸-Dimensión	• DIA 65 x H:256 mm • DIA 80 x H:307 mm
QTY of LEDs-燈珠數量-CANT de LEDs	1 pcs CREE LED Array COB
Input Voltage-輸入電壓-Voltaje de entrada	AC220-240V 50/60HZ or Refer to LED Driver data sheet
Power Consumption Max-燈具功率 Consumo de energía Max	• 5W@DIA 65 x H:256 mm • 8W@DIA 65 x H:256 mm • 6W@DIA 80 x H:307 mm • 9W@DIA 80 x H:307 mm
LED Driver Type LED驅動款式 Tipo de controlador LED	Remote-type LED Driver--Refer to LED driver specification 請參閱LED驅動器規格 Consulte la especificación de controlador de LED 1. ON/OFF Switch AC220-240V 50/60HZ 2. ELV Dimming Driver (5-100%) AC 100-120V 50/60Hz or AC 200-240V 50/60HZ 3. 0-10V Dimming Driver AC100-240V 50/60HZ 4. Dali Dimming Driver AC100-240V 50/60HZ 5. DMX Driver AC100-240V 50/60HZ (Dimming range from 0-100%) 6. RDM Driver AC100-240V 50/60HZ 7. Emergency Backup >2 hours or >3 hours @ < 12 charger hours 應急電池/Copia de seguridad de emergencia
LED Driver Features 驅動特性 Funciones del controlador de LED	POWER FACTOR : PF>0.90 @ Full Load -Refer to LED Driver data sheet TOTAL HARMONIC DISTORTION: THD< 20%- Refer to LED Driver data sheet
Control Protocol-控制協議 Protocolo de Control	1-10V / Dali / DMX 512 / RDM / ZIGBEE Wireless Control
Beam Angle 光束角 ángulo de haz	12° 15° 20° 24° 30° 33° 38° 50°
Light Source Brand-光源品牌-Fuente de luz de marca	CREE- (Photobiological safety-IEC 62471 'Risk Group 1' (low risk))
"Lumen Maintenance LM-80 Reported by TM-21"	L90(10k) = 50,700 hrs L80(10k) > 63,500 hrs L70(10k) > 63,500 hrs
LED Life-LED壽命-La vida del LED	>60,000 hours
Color Temperature -色溫 Temperatura del color	2700K / 3000K / 4000K / 5000K / 6500K
Color Rendering Index-顯色指數 Índice de reproducción cromática	> 80 > 90
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning ellipse	Standard Deviation Colour Matching < 3 SDCM 標準偏差配色 < 3 SDCM Coincidencia de color estándar Desviación < 3 SDCM
Luminaire Efficacy 燈具效率 La eficacia de la luminaria	95 Lm/w(2700K), 100 Lm/w(3000K), 100 Lm/w(4000K), 110 Lm/w(5000K), 110 Lm/w(6500K),
LED Source Luminous Efficacy LED光源光效 Fuente luminosa LED Eficacia	125 Lm/w(2700K), 130 Lm/w(3000K), 130 Lm/w(4000K), 140 Lm/w(5000K), 140 Lm/w(6500K),
Housing materials-外殼材料 Materiales de la carcasa	Die-cast aluminum and acrylic 壓鑄鋁和亞克力 Fundición de aluminio y acrílico
Trim Color-框邊顏色-Estilo Color	Matte white / Matte black 啞光白色 / 啞光黑色 Blanco mate / Matte black
Reflector Color-反光杯顏色-Reflector color	Matte Black / Bright silver / Matte silver 啞黑 / 亮銀 / 啞光銀 Negro Mate / Plata brillante / Plata mate
Ingress Protection-防護等級 Protección de ingreso	IP20
Operating Humidity -工作濕度 Humedad de funcionamiento	0~90%, non-condensing-不結霜 sin condensación
Operating Temperature Range / 工作溫度範圍 Rango de temperatura de funcionamiento	-30 °C / +50 °C
Comply Testing Standard 符合測試標準 Cumplir el estándar de prueba	LED Luminaires: IEC 60598-1 / IEC 60598-2-2 / Photometric data LED Driver: EN 55015 / IEC 61000-3-2 / IEC 61347-1 / IEC 61347-2-13 / IEC 61547
Certification-認證-Certificación	    

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.


Example product code: [AUDORA-6W](#)


AUDORA - -
[Power Consumption](#)

Power Consumption	
Code	Description
5W	5W @ DIA 65mm
8W	8W @ DIA 65mm
6W	6W @ DIA 80mm
9W	9W @ DIA 80mm

BEAM ANGLE

DIMON
TECHNOLOGY





Unit: mm