


BOUK-S

W50xL150xH760 mm 9W



- Main body is made of Die-casting aluminum alloy with Extruded aluminum alloy.
- The diffuser is a soften lens (tempered glass).
- Anti-UV electrostatic powder spraying, regular color: Black & Grey
- Tamper proof fixings for increased vandal resistance.
- IP65 rating water and rust proof protection.

Technical Data

Installation method / 安裝方式 / Tipo de luminaria	Surface Mounted Type / 明裝式燈具 / Superficie Tipo Montado
Dimension / 尺寸 / Dimensión	W:50 x L: 150 x H: 760 mm
Power Consumption Max / 燈具功率 Consumo de energía Max	5W 7W 9W
Input Voltage / 輸入電壓 / Voltaje de entrada	AC 220-240V 50/60Hz
LED Driver Type / LED驅動款式 Tipo de controlador LED	Integrated-type LED Driver--Refer to LED driver specification 請參閱LED驅動器規格 Consulte la especificación de controlador de LED 1. ON/OFF Switch AC220-240V 50/60HZ 2. 0/1 -10V Dimming Driver AC220-240V 50/60HZ 3. DALI Dimming Driver AC220-240V 50/60HZ
LED Driver Features / 驅動特性 Funciones del controlador de LED	Power Factor : PF>0.9
Control Protocol / 控制協議 Protocolo de Control	0/1-10V / DALI
Beam Angle / 光束角 / ángulo de haz	Symmetric
Light Source Brand / 光源品牌 / Fuente de luz de marca	CREE
"Lumen Maintenance LM-80 Reported by TM-21"	<54,000 hours
LED Life-LED壽命-La vida del LED	>100,000 hours
Color Temperature -色溫 Temperatura del color	3000K / 4000K / 5000K / 6500K
Color Rendering Index-顯色指數 Índice de reproducción cromática	>80
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning ellipse	Standard Deviation Colour Matching < 3 SDCM 標準偏差配色< 3 SDCM Coincidencia de color estándar Desviación < 3 SDCM
Luminaire Efficacy / 燈具效率 / La eficacia de la luminaria	• 50 Lm/w (3000K), 55 Lm/w (4000K), • 55 Lm/w (5000K), 60 Lm/w (6500K),
LED Source Luminous Efficacy / LED光源光效 Fuente luminosa LED Eficacia	• 120 Lm/w(3000K), 130 Lm/w(4000K), • 130 Lm/w(5000K), 140 Lm/w(6500K),
Housing materials / 外殼材料 Materiales de la carcasa	Aluminium and Tempered glass 鋁和鋼化玻璃 Aluminio y vidrio templado
Housing Color / 外殼顏色 color de la carcasa	• Black 黑色 Negro • Grey 灰色 Gris
Ingress Protection / 防護等級 Protección de ingreso	IP65
Operating Temperature Range / 工作溫度範圍 Rango de temperatura de funcionamiento	-20 °C / +40 °C
Operating Humidity / 工作濕度 Humedad de funcionamiento	0~90%, non-condensing-不結霜 sin condensación
Comply Testing Standard / 符合測試標準 Cumplir el estándar de prueba	LED Luminaires: IEC 60598-1 / IEC 60598-2-1 / Photometric data-IES format LED Driver: EN 55015 / IEC 61000-3-2 / IEC 61347-1 / IEC 61347-2-13 / IEC 61547
Certification-認證-Certificación	     

Project	Fixture#	Date
		Firm


Ordering Information

Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.



Example product code: [BOUK-S-5W](#)


BOUK-S - -
[Power Consumption](#)

Power Consumption	
Code	Description
5W	5W
7W	7W
9W	9W



BEAM ANGLE





Unit: mm