


DYNISCO


D80x150mm IP20



- LED WALL MOUNTED UP AND DOWN LIGHT.
- Housing: Extrusion aluminium housing with powder coating and die-cast aluminium cover.
- Anti-glare and high purity anodized aluminium reflector to distribute comfortable light
- LED module: high-power CREE LEDs Array, CRI>80, LM-80 performance approval >50,000 hours.
- Integrated-Type 1-10V, DALI, control gear

Technical Data

Luminaire Type-安裝方式-Tipo de luminaria	Wall Mounted Type-壁掛式燈具-Tipo montado en la pared
Dimension-尺寸-Dimensión	DIA: 18 x H: 150 mm (W:108mm with Mounting Bracket)
QTY of LEDs-燈珠數量-CANT de LEDs	• 1 pcs CREE LED COB Array for Up or Down Light • 2 pcs CREE LED COB Array for Up and Down Light
Input Voltage-輸入電壓-Voltaje de entrada	AC220-240V 50/60HZ
Power Consumption Max-燈具功率 Consumo de energía Max	• 7W (1 x 7W) Up or Down Light • 10W (1 x 10W) Up or Down Light • 16W (2 x 8W) Up and Down Light • 20W (2 x 10W) Up and Down Light
LED Driver Type LED驅動款式 Tipo de controlador LED	Integrated-type LED Driver--Refer to LED driver specification 請參閱LED驅動器規格 Consulte la especificación de controlador de LED 1. ON/OFF Switch AC220-240V 50/60HZ 2. 1-10V Dimming Driver AC220-240V 50/60HZ 3. Dali Dimming Driver AC220-240V 50/60HZ 4. Remoted Emergency Backup >2 hours or >3 hours 應急電池/Copia de seguridad de emergencia
Control Protocol-控制協議 Protocolo de Control	1-10V / Dali
Beam Angle 光束角 ángulo de haz	10° 24° 38° 60°
Light Source Brand-光源品牌-Fuente de luz de marca	CREE - (Photobiological safety-IEC 62471 'Risk Group 1' (low risk))
Photobiological safety-IEC 62471 / of Luminaire 光生物安全檢驗(IEC/EN 62471) 結果: Seguridad fotobiológica-IEC 62471	Risk Group 1 (RG1) 1 類危險 (低危) Grupo de riesgo 1
"Lumen Maintenance LM-80 Reported by TM-21"	1. L90(10k) = 50,700 hrs 2. L80(10k) > 63,500 hrs 3. L70(10k) > 63,500 hrs
LED Life-LED壽命-La vida del LED	Ambient temperature ta = 25 °C 50,000 h: L 70 B 50 Ambient temperature ta = 50 °C 50,000 h: L 70 B 50
Color Temperature -色溫 Temperatura del color	2700K / 3000K / 4000K / 5000K / 6500K
Color Rendering Index-顯色指數 Índice de reproducción cromática	> 80 > 90
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning elipse	Standard Deviation Colour Matching < 3 SDCM 標準偏差配色 < 3 SDCM Coincidencia de color estándar Desviación < 3 SDCM
Luminaire Efficacy 燈具效率 La eficacia de la luminaria	70 Lm/w(2700K), 70 Lm/w(3000K), 75 Lm/w(4000K), 80 Lm/w(5000K), 80 Lm/w(6500K),
LED Source Luminous Efficacy LED光源光效 Fuente luminosa LED Eficacia	120 Lm/w(2700K), 120 Lm/w(3000K), 125 Lm/w(4000K), 130 Lm/w(5000K), 130 Lm/w(6500K),
Housing materials-外殼材料 Materiales de la carcasa	Die-cast aluminum & Clear Optical PPMA Lens 壓鑄鋁和 光學 PPMA 鏡頭 Aluminio fundido a presión y lente de PMMA óptico transparente
Housing Color外殼顏色 color de la carcasa	UV resistant Powder Coating :Matte Black RAL 9005 / Matte White RAL 9003 / Matte GrayRAL 9006 抗紫外線粉末塗料: 啞光黑色燈身 RAL 9005 / 啞光白色燈身 RAL9003 / 啞光灰色燈身 RAL 9006 Resistente a los rayos UV Recubrimiento en Polvo: Matte Black RAL 9005 / Matte Blanco RAL 9003 / Gris Mate RAL 9006
Operating Temperature Range / 工作溫度範圍 Rango de temperatura de funcionamiento	-30 °C / +50 °C
Operating Humidity -工作濕度 Humedad de funcionamiento	0~90%, non-condensing-不結霜 sin condensación
Ingress Protection-防護等級 Protección de ingreso	IP20
Comply Testing Standard 符合測試標準 Cumplir el estándar de prueba	LED Luminaries: EN 60598-1;EN 60598-2-1; IEC TR62778 IEC62471 ; IEC 62031; RoHS LED Driver: IEC/EN 61347-1; IEC/EN 61347-2-13; IEC/EN 62384; IEC/EN 61000-3-2; IEC/EN 61000-3-3;IEC/EN61574;EN 55015
Certification-認證-Certificación	



Project	Fixture#	Date
		Firm



Ordering Information


Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.

Example product code: [DYNISCO-10W](#)


DYNISCO- - _____
[Power Consumption](#)

Power Consumption	
Code	Description
7W	7W (1 x 7W) Up or Down Light
10W	10W (1 x 10W) Up or Down Light
16W	16W (2 x 8W) Up and Down Light
20W	20W (2 x 10W) Up and Down Light

BEAM ANGLE




Technical Drawing




Detail:A

Detail:B



Detail:A



Detail:B

Unit: mm