

HAWEY-X

100W-240W Max IP65

CB

IK 08

IP65



0-10V




Option Accessories

PC reflectors
90°PC reflector with lid

Transmittance rate: 85%



Microwave Sensor



Integrated 1-10V Dimming Switch

for 30% 50% 75% 85% 100% Dimming
output selectoin

- Power Selectable Function
- IP65 & IK08 dual protection, corrosion resistance
- 160lm/W or 200lm/W different efficiency for optional for meet different budget.


Technical Data

Luminaire Type-安裝方式/Tipo de luminaria	Mouting by Bracket or Hanging. 安裝支架固定或者吊裝 Soporte de montaje fijo o elevación
Power Consumption with LED Driver LED燈具包括LED驅動電源功率 Consumo de energía con controlador de LED	• 100W (100/80/60W Power Selectable Function) • 150W (150/120/90W Power Selectable Function) • 200W (200/160/120W Power Selectable Function) • 240W (240/190/145W Power Selectable Function)
Input Voltage / 輸入電壓 Voltaje de entrada	220-240VAC/50-60HZ
LED Driver Type LED驅動款式 Tipo de controlador LED	Integrated-type LED Driver--Refer to LED driver specification 請參閱LED驅動器規格 Consulte la especificación de controlador de LED 1. ON/OFF Switch AC220-240V 50/60HZ 2. 0/1 -10V Dimming Driver AC220-240V 50/60HZ 3. DALI Dimming Driver AC220-240V 50/60H 4. Microwave motion sensor 5. PIR sensor
Power Factor / 功率因數/Factor de potencia	PF>0.95
Total Harmonic Distortion/總諧波失/Distorsión armónica total	THD< 15%
Protection Against Surges/防護措施/PROTECCIÓN CONTRA LAS PROMOCIONES:	6kV line-line, 6kV line-earth
Light Source Brand-光源品牌-Fuente de luz de marca	LUMILEDS LED
"Lumen Maintenance LM-80 Reported by TM-21"	L70 > 60,000 Hours
LED Life-LED壽命-La vida del LED	>50,000 hours
Color Temperature 色溫 Temperatura y color	3000K 4000K 5000K 6000K
Color Rendering Index-顯色指數 Índice de reproducción cromática	CRI>70 CRI>80
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning ellipse	Standard Deviation Colour Matching < 3 SDCM 標準偏差配色< 3 SDCM Coincidencia de color estándar Desviación < 3 SDCM
Beam Angle光束角ángulo de haz	60° 90° 120°
Luminaire Efficacy燈具效率 La eficacia de la luminaria	• CRI >80 130 Lm/w(3000K) 140 Lm/w(4000K) 150 Lm/w(5000K) 160 Lm/w(6000K) • CRI >70 160 Lm/w(3000K) 180 Lm/w(4000K) 200 Lm/w(5000K) 200 Lm/w(6000K)
Housing materials外殼材料 Materiales de la carcasa	Die-cast aluminium and Polycarbonate Lens 壓鑄鋁和PC 透鏡 Aluminio fundido a presión y policarbonato
Housing Color外殼顏色/color de la carcasa	Matte Black (RAL9017) 啞光黑色(RAL9017) Negro mate(RAL9017)
Ingress Protection-防護等級 Protección de ingreso	IP65
Mech impact protection機械衝擊保護 Protección contra impactos mecánico	IK08
Operating Temperature Range / 工作溫度範圍 Rango de temperatura de funcionamiento	-30 °C / +50 °C
Operating Humidity -工作濕度 Humedad de funcionamiento	0~100%, non-condensing-不結霜 sin condensación
Dimension/尺寸/Dimensión	Refer to Technical Drawing 請參閱技術圖紙/Consulte Dibujo técnico
Net Weight 淨重/Peso Neto	1.8 kg @ 100W 2.0 kg @ 150W 2.3kg @ 200W 2.6 kg @ 240W
Certificate Standard Complied 符合安規標準 estándar certificado de cumplimiento	LED Luminaries: IEC 60598-1:2017 ; IEC 60598-2-1:1987; IEC TR 62778:2014 (RG1); IEC 62031:2014(LED Modul); IEC 61058-2000 (Sensor); ROHS LED Driver: IEC/EN 61347-1; IEC/EN 61347-2-13; IEC/EN 61347-2-13; EN 55015; EN 61000-3-2;EN 61000-3-3; EN 61547;EN 62384
Certification-認證-Certificación	    


BEAM ANGLE

DIMON
TECHNOLOGY


100W beam angle



(60°)




(90°)




(120°)


150W beam angle



(60°)




(90°)




(120°)


200W-240 beam angle



(60°)




(90°)



(120°)

Technical Drawing



Accessories

Transmittance rate: 85%

DIMON
TECHNOLOGY



PC reflectors
90° PC reflector with lid Code:
00C73A+00C01B
(100W-150W)
Code: 00C01A+00C01B
(200W-240W)



Aluminum Reflector
90° AL reflector
Code: 00D05-01 (100W-150W)
Code: 00D02 (200W-240W)



Safety chain
201 stainless steel, available
for 0.5m long.
Code: C-H54-01



**Zhaga Microwave
Motion Sensor**

zhaga



Zhaga PIR Sensor

zhaga



**CASAMBI ready wireless
module**

zhaga



Microwave motion sensor
12Vdc input, IP65 rating,
max detect height is 15m.
1pin
Code: NT-5-4T



PIR sensor
12Vdc input, IP65 rating, max
detect height is 15m.
1pin
Code: NT-6-4T



Remote controller
For
NT-5-4T
NT-6-4T
Code: C-100



±30° adjustable bracket SPCC
materials with outdoor powder coating.
Code: BC-01



**±45deg adjustable
bracket**
SPCC materials with outdoor powder
coating.
Code: BC-02



Remote controller
For
HD06VCRH 7B/HD06VCRH 7C
Code: D05R