


NOVA-T

75W Max



- Die-casting aluminium body, super white tempered glass, white PC plastic reflector.
- Optics with PC lens with high visual comfortable and uniform lighting distribution, multiple light distribution options.
- High quality LED chips, Driver with 0-10V/DALI/programmed be options, and with surge protection up to 20KV.
- There are a variety of mounting brackets options, form of different shapes of lighting.
- Top and side fixing, angle can be adjustable, installation tube diameter Ø60/Ø76mm.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, (no risk linked to infrared, blue light and UV radiation) in accordance with EN 62471:2008.
- Street lighting control used with smart control technology. It can be compatible with remote management system.
- All external screws are made of 304 stainless steel.

Technical Data

Luminaire Type- 安裝方式 Tipo de luminaria	Pole Mounted: 3-6m燈杆安裝: 3-6m montado en poste: 3-6m		
Power Consumption with LED Driver LED燈具包括LED驅動電源功率 Consumo de energía con controlador de LED	40W 60W 75W		
Input Voltage / 輸入電壓 Voltaje de entrada	100 ~ 240VAC (50~60HZ)		
Control Protocol/控制協議 Protocolo de Control	SW: ON/OFF Switch Driver DA: Dali Dimming Driver RDM : RDM Dimming Driver MS: Motion Sensor	AN: 1-10V Dimming Driver DMX: DMX 512 Dimming Driver ZI: ZIGBEE Wireless Control DS: Daylight Sensor	
Power Factor / 功率因數/Factor de potencia	PF>0.9		
Total Harmonic Distortion/總諧波失/Distorsión armónica total	THD		
Protection Against Surgers/防護措施/PROTECCIÓN CONTRA LAS PROMOCIONES:	Line-Earth:6KV Line-Line:4KV		
Light Source Brand-光源品牌-Fuente de luz de marca	CREE		
"Lumen Maintenance LM-80 Reported by TM-21"	L70 > 45,000 Hours		
LED Life-LED壽命-La vida del LED	>50,000 hours		
Color Temperature 色溫 Temperatura y color	3000K / 4000K / 5000K / 5700K		
Color Rendering Index-顯色指數 Índice de reproducción cromática	>80		
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning elipse	Standard Deviation Colour Matching 3 SCDM 標準偏差配色 3 SCDM Coincidencia de color estándar Desviación		
Beam Angle 光束角 ángulo de haz	Optical Type : A1 A2 A3 A4		
Luminaire Efficacy燈具效率 La eficacia de la luminaria	120 Lm/w(3000K) 125 Lm/w(4000K) 130 Lm/w(5000K) 130 Lm/w(5700K)		
Housing materials 外殼材料 Materiales de la carcasa	Die-cast aluminium alloy and tempered glass 壓鑄鋁和鋼化玻璃 Aluminio fundido a presión y Vidrio templado		
Housing Color 外殼顏色 color de la carcasa	Anti Corrosion Polyester powder 防腐噴粉 Black RAL 9005; Grey RAL 9006; White RAL 9003; Dark Grey RAL 7043 黑色 RAL 9005 灰色 RAL 9006 白色 RAL 9003 深灰色RAL 7043		
Ingress Protection-防護等級 Protección de ingreso	IP66 - (IEC 60529)		
Mech impact protection 機械衝擊保護 Protección contra impactos mecánicos	IK08		
Operating Temperature Range / 工作溫度範圍 Rango de temperatura de funcion amiento	-30 °C / +50 °C		
Operating Humidity -工作濕度 Humedad de funcionamiento	0~90%, non-condensing-不結霜 sin condensación		
Installation Height 安裝高度Altura de montaje	3-6 M		
Dimension 尺寸 Dimensión	Refer to drawing 參考圖紙		
Certificate Standard Complied 符合安規標準 estándar certificado de cumplimiento	LED Luminaries: IEC/EN 60598-1 ; IEC/EN 60598-2-3; IEC TR 62778; IEC 62031 LED Driver: IEC 61347-1; IEC 61347-2-13; EN 55015; IEC 61000-3-2;IEC 61000-3-3; IEC 61547;EN 62384		
Certification-認證-Certificación	CE IK 08 IP66 0-10V DALI 		

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.





Example product code: [NOVA-T-60W](#)


NOVA-T - -

POWER
CONSUMPTION

POWER CONSUMPTION	
Code	Description
40W	40W
60W	60W
75W	75W

BEAM ANGLE





Unit: mm