


PARY

D94 x H90mm 9W

IP20 



Housing: die-cast aluminium, powder-coated, designed as heat sink. Anti-glare Lens system made of PMMA. CRI>90, LM-80 performance approval >50,000 hours.

Technical Data

Luminaire Type- 安裝方式 Tipo de luminaria	E27 Connector E27接頭 E27 Conector
Dimension-尺寸-Dimensión	DIA 94 x H:90 mm
QTY of LEDs-燈珠數量-CANT de LEDs	<ul style="list-style-type: none"> • 1 pcs CREE LED Array • 12 pcs Philips High Power LED
Input Voltage-輸入電壓-Voltaje de entrada	AC220-240V 50/60HZ
Power Consumption Max-燈具功率 Consumo de energía Max	<ul style="list-style-type: none"> • 9W Cree • 10W Philips LED
LED Driver Features 驅動特性 Funciones del controlador de LED	EFFICIENCY (Typ.): >85% MAX. No. of PSUs on 16A CIRCUIT BREAKER: 35 units (circuit breaker of type B) / 50 units (circuit breaker of type C at 230VAC)
Beam Angle 光束角 ángulo de haz	<ul style="list-style-type: none"> • 15° -CREE COB • 24° -CREE COB • 36° -Philips 12 x LEDs • 45° -Philips 12 x LEDs
Light Source Brand-光源品牌-Fuente de luz de marca	<ul style="list-style-type: none"> • CREE- (Photobiological safety-IEC 62471 'Risk Group 1' (low risk)) • Philips
"Lumen Maintenance LM-80 Reported by TM-21"	1. L90(10k) = 50,700 hrs 2. L80(10k) > 63,500 hrs 3. L70(10k) > 63,500 hrs
LED Life-LED壽命-La vida del LED	>60,000 hours
Color Temperature -色溫 Temperatura del color	2700K / 3000K / 4000K / 5000K / 6500K
Color Rendering Index-顯色指數 Índice de reproducción cromática	> 90
MacAdam Ellipses Binning 麥克亞當橢圓分級 Mac Adam binning elipse	Standard Deviation Colour Matching < 3 SDCM 標準偏差配色 < 3 SDCM Coincidencia de color estándar Desviación < 3 SDCM
Luminaire Efficacy 燈具效率 La eficacia de la luminaria	<ul style="list-style-type: none"> • 95 Lm/w(2700K), • 100 Lm/w(3000K), • 100 Lm/w(4000K), • 105 Lm/w(5000K), • 105 Lm/w(6500K),
LED Source Luminous Efficacy LED光源光效 Fuente luminosa LED Eficacia	105 Lm/w(2700K), 110 Lm/w(3000K), 110 Lm/w(4000K), 120 Lm/w(5000K), 120 Lm/w(6500K),
Housing materials-外殼材料 Materiales de la carcasa	Die-cast aluminum and acrylic 壓鑄鋁和亞克力 Fundición de aluminio y acrílico
Housing Color 外殼顏色 color de la carcasa	Powder Coating : White 粉末塗料: 白色 Recubrimiento en Polvo: Cuerpo blanco
Ingress Protection-防護等級 Protección de ingreso	IP20 - (IEC 60529)
Environment-使用環境-medio ambiente	Indoor
Certification-認證-Certificación	<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 2px 5px; margin-right: 10px;">IP20</div> </div>

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.

Example product code: [PARY-9W-SW-S-30](#)

PARY - - _____ - _____ - _____ - _____
Power Consumption
LED Driver Type
BEAM Angle
Color Temperature

Power Consumption		LED Driver Type		BEAM Angle		Color Temperature	
Code	Description	Code	Description	Code	Description	Code	Description
9W	CREEE COB	SW	ON/OFF Switch	N	15°	27	2700K
10W	PHILIPS LEDs	ELV	ELV Leading Edge Control	S	24°	30	3000K
				M	36°	40	4000K
				L	45°	50	5000K
						65	6500K

